

144 CHANNELS CELL SIMULATION RACK/MODULE CS 31-1-144

OVERVIEW

The Cells Simulation Rack/Module is a battery simulator module with 144 isolated cells used to simulate battery features. The voltage of each cell can be adjusted through Standard CAN, Ethernet TCP and USB-C, as well as getting the voltage and the current measurements.

A single module can be used or several in series according to the requirements (based on how many cells are needed). Also, the module can be used independently or in a mountable rack system.

KEY FEATURES

- 144 independent and isolated cells in total.
- Extendable number of cells by adding more modules in series.
- Standalone module or bench rack mounted.
- Each cell has an adjustable output voltage of 0 V to 7 V with 1.0 mV precision.
- The current sourcing of each cell is up to 1 A.
- Voltage measurement with a precision of 0.4 mV.
- High current measurement with a precision of 1mA.
- Low current measurement with a precision of 20 uA.
- Controllable by CAN ISO 11898-2, Ethernet TCP and USB-C.



DIMENSION

L*W*H = 55cm*70cm*113.7cm

OPERATING TEMPERATURE

-20 °C ~ +60 °C

POWER REQUIREMENT

DC power supply: 24 VDC

DETAILED SPECIFICATIONS:

Cell Voltage Output	Value	Unit
Range	0 to 7	V
Stability Precision	1000	μ V
Setting Precision	1000	μ V
Isolation Voltage	1500, Tested for 1 minute and 1mA max	V

Cell Discharge Current	Value	Unit
Range	0 to 1	A

Cell Charge Current	Value	Unit
Range	500	mA

Cell Voltage Measurement	Value	Unit
Range	-7 to 7	V
Resolution	16	bit
Precision	400	μ V

Low Cell Current Measurement	Value	Unit
Range	-1 to 1	mA
Resolution	16	bit
Precision	20	μ A

High Cell Current Measurement	Value	Unit
Range	-1000 to 1000	mA
Resolution	16	bit
Precision	1	mA

ENVIRONMENTAL

The Cells Simulation module is intended for indoor use only but may be used outdoors if installed in a suitable enclosure. Refer to the manual for more information about meeting these specifications.

Operating temperature

-40°C--+55°C

Storage temperature

-40°C--+85°C

Ingress protection (IP code)

None

Operating humidity

10-90% RH non condensing

Storage humidity

5-95% RH non condensing

DIMENSION

L*W*H = 55cm*70cm*113.7cm



ART Logics (Shanghai) Testing Equipment CO., Ltd

艾驰电子检测设备技术（上海）有限公司

Tel: 021-61075469

Room 105, No. 258, Chengjiaqiao Road, Shanghai, P.R. China



www.art-logics.com

support@art-logics.com